

### Audio

A 103 dB(A) limit must be maintained at all times due to local regulations.  
Please respect these rules. Dynamo measurement tools and technicians are always leading.

#### Power

40A 3 Phase for all Audio (2x16A for backline)

#### PA-System: Processor settings made by Dynamo only

Tops	6	JBL VTX V25-II
Subs	3	JBL VTX S25
Infills	2	Adamson M12
Amplifiers	3	Crown I-Tech 4x3500HD
Input Options		Left Right (Analog); Left Right Sub Infill (AES)

#### FOH Console

Console	1	Allen&Heath Dlive C3500
Stagerack	1	Allen&Heath Dlive CDM48
I/O Card	1	Allen&Heath 64x64 Dante Card @ C3500
I/O Card	1	Allen&Heath AES4I6O @ CDM48

#### Monitor Console

Console	1	Allen&Heath Dlive C3500
Stagerack	1	Allen&Heath Dlive CDM48
I/O Card	1	Allen&Heath AES4I6O @ CDM48

#### Monitor System

Wedges	8	Adamson M12 (bi-amped)
Processors	2	Xilica XP4080
Amplifiers	2	Labgruppen FP10000Q (low)
Amplifiers	2	Powersoft M50Q (High)

### Audio

#### Microphones

Shure SM58	5
Shure SM57	5
Shure Beta 52	2
Shure Beta 91	2
Shure Beta 57	3
Sennheiser E904	6
Sennheiser E914	2
Sennheiser E906	2
Sennheiser E945	2
Sennheiser MD421	2
AKG C214	2

#### DI's

BSS AR133	6
Radial Pro 2 Stereo	2

#### Stands:

K&M Tall	8
K&M Mid	14
K&M Low	2

### Lights

#### Power (on stage)

In use for House installation	3	40A (63A cee 5pole plug)
In use for House installation	3	16A
Free	1	63A (63A cee 5pole plug)
Free	3	16A
Dimmers	4	Lightec SP12 12ch dimmerpack 2kw (48 dimmers total)
Dimmers	2	Electron e1550dc (12 dimmers total)

#### Stage

Elation PlatinumSpot 5R-Pro (extended mode)	8
Coemar Prospot lx	4
Ledwash Eurolite TMH-12 (12ch mode)	8
Par 64 500w MFL	42
ADJ Freq Matrix	6

#### Hall

Ledwash Eurolite TMH-12 (12ch mode)	6
Ledwash Eurolite TMH-9 (12ch mode)	20
Fresnell 1000w	4
Par 64 500w MFL	18
Ayra ero 706	6
Ledpar Showtec (balcony)	11

### Lights

#### Free

Floorspot 500w MFL	8
Ayra Ero 706	8
ETC Source Four 575w	2
Hazer 1500w (dmx)	2
Smokemachine 2000w (dmx)	1
Mirrorbal 1m	1
Mirrorbal 0.5m	6

#### Light Desk

Avolites Arena	1
----------------	---

#### Lee Filter list

Available gels for par64:

027	129 (frost)	147	201
104	132	152	204
116	135	156	707
120	136	161	
122	139	170	
126	141	181	

### Video

#### Fixed installation (see drawing)

Beamer Epson EB-G6050W (fixed installation)	1
Electric videoscreen 4x2,5 m on stage (fixed installation)	1

- We can only provide HDMI and VGA(d-sub15) connections (link to FOH or balcony is possible).

### Stage elements

Main stage is fixed! (1 meter)

#### Loose elements:

2x1 meter (excl. stands)	12
Stands 0.40 meter	48
Stands 0.60 meter	24
Stands 0.80 meter	24
Stands 1 meter	48
Clamps	22

### Dimensions

Stage	10 x 3,5 m, clearance 5,5 meter max
Hall	10 x 12 m, clearance 6,5 meter max
Balcony	10 x 3 m, clearance 2,5 meter max

#### Max. Load-in Dimensions:

Door to Stage	1.75 x 2.00 m (w*h)
Door to Hall	1.75 x 2.00 m (w*h)

